

Turf tyres Rib

CLICK HERE TO BUY THESE TYRES ONLINE NOW FROM WWW.ALLTERRAINTYRES.CO.UK

Dimension	PR/LI	Tread pattern	TL/TT	Sales unit	57 07562 +	mm	mm	kg	km/h	bar	
4"											
11x4.00-4	2PR	ST-31	TL	Tyre	128108	269	102	90	16	1.75	2.10
	4PR	ST-31	TL	Tyre	278452	287	104	326	16	2.30	2.5
5"											
11x4.00-5	2PR	ST-31	TL	Tyre	130385	277	105	100	16	1.50	3.00
6"											
13x5.00-6	4PR	ST-31	TR13	Set	130446	326	126	200	16	2.80	3.50
13x6.50-6	4PR	ST-31	TR13	Set	130477	337	168	210	16	1.80	4.50
15x6.00-6	4PR	ST-31	TR13	Set	130521	364	151	260	16	2.10	4.50
8"											
16x6.50-8	4PR	ST-31	TR13	Set	130576	416	169	280	16	1.80	5.3751
18x8.50-8	4PR	ST-31	TL	Tyre	128429	447	211	370	16	1.50	7.001
18x9.50-8	4PR	ST-31	TL	Tyre	128498	457	231	470	16	1.75	7.001
10"											
20x8.00-10	8PR	Carlisle Rib Tread	TL	Tyre	151557	516	206	1673	16	5.60	6.00
20x10.00-10	4PR	ST-31	TL	Tyre	265537	500	240	530	16	1.50	8.00
12"											
26x12.00-12	4PR	Carlisle Hi-Flotation I-1	TL	Tyre	132082	648	297	800	16	1.30	10.501



Variation in load carrying capacity with speed.

	kg	km/h ->	0	10	15	20	25	30	35	40	45
A4 LLV	% ->		+65	+20	+12	0	-2	-5			
A4 HLV	% ->		+98	+44	+34	+20	+17	+14			
A6 LLV	% ->		+65	+29	+21	+14	+7	0	-5	-10	
A6 HLV	% ->		+98	+55	+45	+37	+28	+20	+14	+8	
A8 LLV	% ->		+65	+40	+33	+26	+19	+12	+5	0	-5
A8 HLV	% ->		+98	+68	+60	+51	+43	+34	+26	+20	+14

Ag./Impl.

LLV = Low Load Variation

HLV = High Load Variation

Source: ETRTO



Kenda K401

Carlisle Hi-flotation I-1

Carlisle Rib Tread

Turf tyres

Slicks

CLICK HERE TO BUY THESE TYRES ONLINE NOW FROM [WWW.ALL TERRAIN TYRES.CO.UK](http://WWW.ALLTERRAIN TYRES.CO.UK)

Dimension	PR/LI	Tread pattern	TL/TT	Sales unit	57 07562 +	mm	mm	kg	km/h	bar	
4"											
4.10/3.50-4	4PR	Kenda K404	TL	Tyre	265742	257	94	160	16	3.50	2.50
8x3.00-4	4PR	ST-30	TL	Tyre	130361	210	67	170	16	3.50	2.10
9x3.50-4	4PR	ST-30	TL	Tyre	130378	235	101	140	16	3.50	2.10
	4PR	Kenda K404	TL	Tyre	128061	229	94	160	16	3.50	2.75
	4PR	Carlisle Smooth	TL	Tyre	265346	221	94	118	16	3.45	2.50
5"											
11x3.60-5	4PR	ST-30	TT	Tyre	265353	280	92	165	16	3.50	3.00
11x4.00-5	4PR	ST-30	TL	Tyre	128146	285	100	148	16	3.20	3.00
	4PR	Kenda K404	TL	Tyre	130392	285	100	148	16	3.20	3.00
	4PR	Carlisle Smooth	TL	Tyre	264516	279	102	148	16	3.17	4.00
12x4.00-5	4PR	ST-30	TT	Tyre	265360	300	100	175	16	3.50	3.00
100/75-5	42A8	Trelleborg T522	TL	Tyre	268835	282	103	150	40	3.15	3.00
6"											
13x4.00-6	4PR	ST-30	TT	Tyre	265377	325	90	205	16	3.50	3.50
13x5.00-6	4PR	Carlisle Smooth	TL	Tyre	264530	323	122	200	16	2.76	4.50
13x6.50-6	4PR	Carlisle Smooth	TL	Tyre	264547	328	150	209	16	1.93	3.75
8"											
4.00-8	4PR	ST-30	TT	Tyre	130019	398	100	300	16	3.00	2.50A
5.00-8	4PR	ST-30	TT	Tyre	130224	445	144	325	16	3.50	3.00D
18x9.50-8	4PR	ST-30	TL	Tyre	128511	458	236	470	16	1.70	7.00I
	4PR	Carlisle Smooth	TL	Tyre	264752	450	236	473	16	1.66	7.00
21x12.00-8	40F (4PR)	ST-30	TL	Tyre	269085	525	255	140	80	0.40	8.50
10"											
18x10.50-10	2PR	Carlisle Smooth	TL	Tyre	264646	460	254	332	16	0.83	8.50
20x10.00-10	2PR	Carlisle Smooth	TL	Tyre	264783	498	241	371	16	0.83	8.00
	4PR	Kenda K404 LG	TL	Tyre	265544	503	205	530	16	1.50	8.00
12"											
24x13.00-12	4PR	Carlisle Smooth	TL	Tyre	265100	602	333	787	16	1.24	10.50



Carlisle Smooth
Kenda K404
Trelleborg T522